



RECYFIX®PRO 100

RECYFIX®PRO 100, class B 125, Type 01 with GUGI-Grating made of PA-GF, MW 15/25, black, locked



B 125



■ Technical data:

Length mm	Width mm	Height mm	Weight kg	Inlet cross-section cm ² /m	Drainage cross-section cm ²	Inlaying depth	Item-no.
1000	160	150	4,26	444	92	20	47035

■ Product description:

RECYFIX PRO 100 type 01 - channel made of modified PP, with integrated angle housing, with vertical connection possibility DN/OD 110, with GUGI-mesh grating, mesh width 15/25, black, with horizontal thrust resistance and locking device, loading capacity from A 15 - B 125 according to EN 1433, L/W/H 1000x160x150 mm, item no. 47035

■ Material:

- **Channel body:** modified Polypropylene
- **Bolts:** Steel black galvanised
- **Locking handle:** RECYFIX Material (recycled PA)
- **Grating:** reinforced Polyamide

■ Type acc. DIN EN 1433:


M

■ Set of rules:

DIN 19580/EN 1433

■ Application areas:

- Railway platform
- Facade drainage
- Flat roofs, terraces and balconies
- Pedestrian zones
- Gardening and landscaping



- Multi storey car parks
- Market squares, markets
- Public areas and squares
- Cityscapes with architectural value
- Cycle paths and footpaths
- School yards
- Access drives private